

SITOP PSU100L 24 V/5 A
 SITOP PSU100L 24 V/5 A STABILIZED POWER SUPPLY INPUT:
 120/230 V AC OUTPUT: 24 V/5 A DC



Input	
Input	1-phase AC
Supply voltage	
<ul style="list-style-type: none"> • 1 at AC Rated value • 2 at AC Rated value • Note 	120 V 230 V Set by means of selector switch on the device
Input voltage	
<ul style="list-style-type: none"> • 1 at AC • 2 at AC 	93 ... 132 V 187 ... 264 V
Wide-range input	No
Overvoltage resistance	$2.3 \times V_{in}$ rated, 1.3 ms
Mains buffering at lout rated, min.	20 ms; at $V_{in} = 93/187$ V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	47 ... 63 Hz
Input current	
<ul style="list-style-type: none"> • at rated input voltage 120 V • at rated input voltage 230 V 	2.1 A 1.15 A
Switch-on current limiting (+25 °C), max.	32 A

Duration of inrush current limiting at 25 °C	
• typical	3 ms
I ² t, max.	0.8 A ² ·s
Built-in incoming fuse	T 3,15 A/250 V (not accessible)
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: from 6 A characteristic C

Output

Output	Controlled, isolated DC voltage
Rated voltage V _{out} DC	24 V
Total tolerance, static ±	3 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	0.5 %
Residual ripple peak-peak, max.	150 mV
Residual ripple peak-peak, typ.	50 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	240 mV
Spikes peak-peak, typ. (bandwidth: 20 MHz)	150 mV
Adjustment range	22.8 ... 26.4 V
Product function Output voltage adjustable	Yes
Output voltage setting	via potentiometer
Status display	Green LED for 24 V OK
On/off behavior	Overshoot of V _{out} approx. 4 %
Startup delay, max.	1.5 s
Voltage rise, typ.	130 ms
Rated current value I _{out} rated	5 A
Current range	0 ... 5 A
• Note	+45 ... +60 °C: Derating 2%/K
Supplied active power typical	120 W
Parallel switching for enhanced performance	Yes
Numbers of parallel switchable units for enhanced performance	2

Efficiency

Efficiency at V _{out} rated, I _{out} rated, approx.	86 %
Power loss at V _{out} rated, I _{out} rated, approx.	17 W

Closed-loop control

Dynamic mains compensation (V _{in} rated ±15 %), max.	0.3 %
Dynamic load smoothing (I _{out} : 10/90/10 %), U _{out} ± typ.	2 %
Load step setting time 10 to 90%, typ.	0.4 ms
Load step setting time 90 to 10%, typ.	0.4 ms

Protection and monitoring

Output overvoltage protection	< 33 V
Current limitation, typ.	5.25 A

Property of the output Short-circuit proof	Yes
Short-circuit protection	Constant current characteristic
Enduring short circuit current RMS value <ul style="list-style-type: none"> • typical 	8 A
Overload/short-circuit indicator	-

Safety

Primary/secondary isolation	Yes
Galvanic isolation	Safety extra-low output voltage U_{out} acc. to EN 60950-1 and EN 50178
Protection class	Class I
Leakage current <ul style="list-style-type: none"> • maximum • typical 	3.5 mA 0.4 mA
CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259
Explosion protection	-
FM approval	-
CB approval	Yes
Marine approval	-
Degree of protection (EN 60529)	IP20

EMC

Emitted interference	EN 55022 Class A
Supply harmonics limitation	-
Noise immunity	EN 61000-6-2

Operating data

Ambient temperature <ul style="list-style-type: none"> • during operation — Note • during transport • during storage 	0 ... 60 °C with natural convection -40 ... +85 °C -40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, no condensation

Mechanics

Connection technology	screw-type terminals
Connections <ul style="list-style-type: none"> • Supply input • Output • Auxiliary 	L, N, PE: 1 screw terminal each for 0.5 ... 2.5 mm ² single-core/finely stranded +, -: 2 screw terminals each for 0.5 ... 2.5 mm ² -
Width of the enclosure	50 mm
Height of the enclosure	125 mm
Depth of the enclosure	120 mm
Required spacing	

<ul style="list-style-type: none"> • top • bottom • left • right 	<p>50 mm</p> <p>50 mm</p> <p>0 mm</p> <p>0 mm</p>
Weight, approx.	0.5 kg
Product feature of the enclosure housing for side-by-side mounting	Yes
Installation	Snaps onto DIN rail EN 60715 35x7.5/15
MTBF at 40 °C	3 076 166 h
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)